



Model	730ZT	731ZT
Sensitivity (mV/m/s <sup>2</sup> )	1.0 ±10%	10.0 ±10%
Transverse Sensitivity (max)	< 5%	
Noise Floor (max)	< 20μVrms	< 40μVrms
Operating Temperature range	-50°C to 120°C	-50°C to 110°C
Frequency Response (±3dB)	0.5Hz to 15kHz (X, Y), 0.5Hz to 20kHz (Z)	0.5Hz to 10kHz (X, Y), 0.5Hz to 18kHz (Z)
Resonance Frequency	< 55kHz (Z)	
Measurement Range (m/s <sup>2</sup> )	±5,000	±450
Max. operational shock (m/s <sup>2</sup> )	< 30,000	
Output Impedance	< 100 ohm	< 500 ohm
Ground	Case ground	
Cables	Proprietary cable	
Connector	CZ664	
Material	Titanium	
Dimension (W × H × D)	10mm x 10mm x 10mm (Connector excluded)	
Weight	Approx. 4.4g	
Accessories	Mounting screw (M3 x 0.5 x 4) 1 pc. Mount base (ABS resin, 19mm x 19mm) 1 pc. Proprietary cable CL-730B (3m, 4P-BNC) 1 pc.	

UNIT mm
ANGLE
SCALE
:

730ZT/731ZT

**TEAC** ティアック株式会社