

Are You Ready for DICOM Integration?



Medical Grade Digital Video Recorder

UR-4MD

Designed for the mission critical OR environment

Full HD

1920 x 1080

Video and Photo recording

Advanced
Reliability
w/ Fail-safe recording

Gateway*


Modality Worklist support

3.5 inch
Built-in LCD Display

Simultaneous recording USB & iHDD

Plug & Play Automatic configuration

* DICOM Gateway is an optional upgrade.



Key Features

- Crystal Clear, Full HD 1920 x 1080, Video & Photo Recording
- 3.5" built-in LCD Display for Live-view/Playback/Navigation
- Auto-Signal Detection & Auto-Resolution setting
- Safe Recording to iHDD, USB devices and Network drive simultaneously.
- Networking (FTP & CIFS) RJ45 10/100/1000 Ethernet
- Remote control via Scope, Foot-pedal, Barcode-reader or Keyboard (Optional)
- PACS connectivity: DICOM Storage & MWL support (Optional)
- Medical Standards

Product Overview

UR-4MD is TEAC's latest high-definition medical video recorder designed for quick set up and ease of use, yet includes a robust list of features and capabilities. With auto sensing video connections and automatic video resolution detection, set up is quick and easy.

The front control panel allows users to intuitively record videos and photos in crystal clear HD. A built-in hard drive is included for reliable recording, data back-up and users can also simultaneously record to USB memory and USB hard drives to archive, share and play back on other devices and locations. UR-4MD is also Network capable. With an optional upgrade, DICOM integration is made easy.

Recording Times (for a 500GB Hard Drive)

High-Definition 1920 x 1080		
12 Mbps	18 Mbps	24 Mbps
90 hours	60 hours	45 hours
Standard-Definition 640 x 480		
5 Mbps	8 Mbps	10 Mbps
180 hours	135 hours	100 hours
		Times are approximate.

UR-4MD Digital Video Recorder





Rear view

Specifications Storage & Display USB Flash Drive, USB Hard Drive Recordable Devices Internal Hard Drive (500GB) *1TB Optional Upgrade available Built-in LCD Display 3.5 inch Full Color Recording Format (FAT32) Photo JPEG, DICOM JPG, DCM Video MPEG-4 AVC/H.264 Input/Output 3G/HD-SDI: 1080p/1080i/720p, SD-SDI: 480i/576i SDI (BNC) x1 Input/ Output DVI (Single Link) x1 High-Definition Video NTSC. PAI S-Video x1 Composite (BNC) x1 NTSC, PAI Output SDI Thru x1 SDI (BNC) x1 * SDI video output terminal used in common. Input/ Output Audio Stereo mini jack x1 Stereo mini jack x1 MIC Input RJ-45 (10BASE-T/100BASE-TX/1000BASE-T) x1 2 front connectors for Recordable Devices USB2.0 Type A x3 1 rear connector for Optional Accessories Other Interfaces 1 rear connector for accessing the internal USB 2.0 Type B x1 Hard Drive (on UR-4MD) Stereo mini jack x3 for external trigger General AC 100V - 240V, 50/60Hz Power supply Dimensions (WxDxH Approx. 8 1/4 x 9 1/4 x 3 3/8 in (210.5 x 235 x 88.5 mm) Approx. 5.7 lbs. (2.6 kg) Weight UL60601-2003, CE, IEC60601-1, CSA60601-1, EN60601-1 Certifications EMC IEC60601-1-2, EN60601-1-2, ICES-003, FCC Class B Category FDA Class 1, ANVISA, RoHS, CCC What's in the box TEAC UR-4MD, Power cords, Cable clamp, Owner's manuals Accessories (Optional) Remote control unit, Foot-switch, Keyboard, Barcode / Card Reader

"Blu-rayTM Disc", "Blu-rayTM" and "Blu-rayTM Disc" logo are trademarks of Blu-rayTM Disc Association. Other company names, product names and logos in this document are the trademarks or registered trademarks of their respective owners. *Features and specifications are subject to change without notice.

TEAC EUROPE GmbH.

Bahnstrasse 12, 65205 Wiesbaden-Erbenheim, Germany

Tel.: +49-(0)611-7158-349 Fax: +49-(0)611-7158-392 Email: ipd-sales@teac.eu https://teac.eu/en/